

# POCKETWORKS

## Pocket Silk

### LUBRICATION RANGE

## Polish and maintenance tool

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.



#### SECTION 1

Product name  
Product Use

#### PRODUCT IDENTIFICATION

Pocketworks Silk  
Polish, lubricant, mould release agent.



#### SECTION 2

Classification 1272/2008/EC

Environment

Hazard symbols:

Hazard statements:

Precautionary statements:

#### HAZARDS IDENTIFICATION

Physical and Chemical Hazards

Human health

Aquatic Chronic 2; H411

Signal word: Danger

H222

H229

H315

H336

H411

P210

P211

P251

P410+412

P271

P273

P280

P302+352

P501

Flam. Aerosol 1, H222

Sk.Irrit.2;H315; STOT SE3;H336

Contains: Hydrocarbons, C6, Isoalkanes, <5% n-Hexane.

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects

Keep away from heat/sparks/open flames/hot surfaces – No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Use only outdoors or in a well ventilated area.

Do not release to the environment.

Wear protective gloves.

IF ON SKIN: Wash with plenty of water.

Dispose of contents/container in accordance with local/national regulations.



#### SECTION 3

Hazardous components

Hydrocarbons, C6,  
Isoalkanes, <5% n-Hexane

Liquefied Petroleum Gas

#### COMPOSITION

Related In

% (w/w)

CAS no.

Classification

H-Statements

35-55

64742-49-0

Flam.Liq. 2; STOT SE 3; Asp. Tox. 1; H225; H336; H304; H315; H401; H411  
Sk.Irrit.2; Aq. Acute 2; Aq.Chron. 2

30-50

68476-85-7

Flam.Gas 1; Gas under pressure

H220; H280



#### SECTION 4

In cases of contact

Eyes

Ingestion

Inhalation

Skin

#### FIRST AID MEASURES

Flush with water for 15 minutes. Seek medical advice if irritation persists.

Do not induce vomiting. Give water to drink. Seek medical advice.

Remove to fresh air, keep warm, and seek medical advice.

Wash with soap and water. Seek medical advice if irritation develops.



#### SECTION 5

Extinguishing media

Special procedures

#### FIRE FIGHTING MEASURES

Use Carbon Dioxide, Dry Powder or Foam.

Wear self-contained breathing apparatus for chemical fires. Use water spray to keep containers cool.



#### SECTION 6

Clean-up procedures

#### ACCIDENTAL RELEASE MEASURES

Eliminate all sources of ignition. Do not discharge into drains or rivers. Absorb into dry earth or sand.

Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**SECTION 7**

Handling

**HANDLING AND STORAGE**

Ensure there is sufficient ventilation of the area. Smoking is forbidden. Avoid prolonged or repeated contact with skin.

Storage

Store in cool, well ventilated area, below 50°C. Keep away from ignition sources.

**SECTION 8**

Hazardous components

Chemical name

Hydrocarbons, C6,  
Isoalkanes, <5% n-Hexane  
Butane

Engineering measures

Respiratory protection

Hand protection

Eye protection

Skin protection

**EXPOSURE CONTROLS AND PERSONAL PROTECTION**

Workplace exposure limits (WELs)

8 hour TWA

15 min STEL

Related information

1000 mg m-3

1450 mg m-3

1810 mg m-3

Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.

Protective gloves.

Wear safety glasses if there is a risk of eye contact.

Protective overalls.

**SECTION 9**

State: Aerosol

Flash point °C: &lt;0

**PHYSICAL AND CHEMICAL PROPERTIES**

Odour: Hydrocarbon

Colour: Colourless

Solubility in water: Insoluble

Flammability limits: 0.8% – 9.0%

**SECTION 10**

Stability

Conditions to avoid:

Materials to avoid

Decomposition products

**STABILITY AND REACTIVITY**

Stable under normal conditions.

Hot surfaces. Sources of ignition. Flames.

Strong acids. Strong bases. Oxidising agents.

Oxides of carbon.

**SECTION 11**

Skin

Eye

Ingestion

Inhalation

**TOXICOLOGICAL INFORMATION**

Contact may cause irritation and redness. Prolonged or repeated contact may defat the skin leading to dermatitis.

Contact may cause irritation and pain.

Nausea and stomach pain may occur. There may be irritation of the mouth, throat and digestive tract.

May cause upper respiratory tract irritation if high levels of vapour are inhaled.

**SECTION 12****ECOLOGICAL INFORMATION**

The aerosol contents are potentially harmful to aquatic organisms.

**SECTION 13**

Disposal operations

**DISPOSAL CONDITIONS**

Contact licensed waste disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SECTION 14**

UN no: 1950

Shipping name: Aerosols

**TRANSPORT INFORMATION**

Class: 2

Labelling: 2.1

ADR/RID Classification code: 5F

IMDG/IMO EmS: F-D,S-U

Tariff Number: 34039900

**SECTION 15**

Regulatory references:

**REGULATORY INFORMATION**

Regulations (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation EU 453/2010 amending Regulation (EC) No 1907/2006.

**SECTION 16****OTHER INFORMATION**

N.B. This SDS gives a summary of the product's classification and hazards under the CLP Regulations, the full version is available from the office.

Always use in accordance with manufacturer's directions.

Dated 21/07/17

CLP/Rev.1

**Pocketworks** Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire. B78 3RW. Telephone: 0800 707 6434

The **IM Group** utilises a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

**Trademark(s): Pocketworks** is a wholly owned subsidiary and registered trademark of the IM Group.