

FIX IT - Rubber & Plastic

A flexible quick setting high strength epoxy adhesive

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.



SECTION 1

Product name
Product use

PRODUCT IDENTIFICATION

FIX IT - Rubber & Plastic Resin
Epoxy Repair system



SECTION 2

Classification 1272/2008/EC

HAZARDS IDENTIFICATION

Physical and Chemical Hazards Not classified
Human health Sk.Irrit.2; H315; Sk.Sens.1; H317; Eye Irrit.2; H319



Environment
Hazard symbols:
Hazard statements:

Aq.Chronic 2; H411
Signal word: Warning

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H319

Causes serious eye irritation.

H411

Toxic to aquatic life with long lasting effects.



Precautionary statements:

P264

Wash with soap and water thoroughly after handling.

P273

Avoid release to the environment.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

P332+313

If skin irritation occurs: Get medical advice/attention.



SECTION 3

Hazardous components

Chemical Name(s)

Bisphenol A-(Epichlorhydrin)
Reaction product

COMPOSITION/INFORMATION ON INGREDIENTS

Related Information

% (w/w)

>80

CAS no.

25068-38-6

Classification

Sk.Irrit.2

Sk.Sens.1

Eye Irrit.2

Aq.Chronic 2

H Statements

H315

H317

H319

H411



SECTION 4

Contact with

Eyes

Ingestion

Inhalation

Skin

FIRST AID MEASURES

Flush with water for 15 minutes. Seek medical advice if irritation persists.

Do not induce vomiting. Give water to drink. Seek immediate medical advice and show this sheet.

Remove to fresh air for at least 10 minutes.

Wash skin thoroughly with soap and warm water. Dry skin and apply replenishing cream.

Seek medical advice if irritation develops.



SECTION 5

Extinguishing media

Special procedures

FIRE FIGHTING MEASURES

Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.



SECTION 6

Clean-up procedures

ACCIDENTAL RELEASE MEASURES

Mark out the contaminated area with signs and keep unauthorised personnel out. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not discharge into drains or rivers.

**SECTION 7**

Handling
Storage

HANDLING AND STORAGE

Do not eat, smoke or drink whilst working with this material. Wash hands before meals and after work.
Store in a cool, well ventilated area. Keep containers tightly closed.

**SECTION 8**

Engineering measures
Respiratory protection
Hand protection
Eye protection
Skin protection

EXPOSURE CONTROLS/ PERSONAL PROTECTION

No particular engineering measures necessary.
Not normally required.
Protective gloves; check with glove manufacturer for specific advice.
Wear safety glasses or goggles if risk of eye contact.
General workwear.

**SECTION 9**

State: Liquid
S.G.: 1.1

PHYSICAL AND CHEMICAL PROPERTIES

Colour: Pale yellow Odour: Characteristic Solubility in water: Insoluble pH: N/A
Boiling Pt.: >85°C Flash Pt.: >80°C Viscosity : Viscous

**SECTION 10**

Stability
Conditions to avoid
Materials to avoid
Decomposition products

STABILITY AND REACTIVITY

Stable under normal conditions.
Hot surfaces. Sources of ignition. Flames.
Strong oxidising agents. Strong acids.
Combustion will generate oxides of carbon, acrid smoke and irritating fumes.

**SECTION 11**

Hazardous ingredients
Routes of exposure:

TOXICOLOGICAL INFORMATION

Bisphenol A-(Epichlorhydrin) Reaction product, ORL RAT LD50 11400 mg/kg
Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases.

**SECTION 12****ECOLOGICAL INFORMATION**

Persistence and degradability: Not biodegradable. Toxic to aquatic organisms.

**SECTION 13**

Disposal operations

DISPOSAL CONSIDERATIONS

Contact licensed waste disposal company. Treat as controlled waste.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SECTION 14**

UN no: 3082
Shipping name:

TRANSPORT INFORMATION

Class: 9 PG: III Labelling: 9 ADR/RID Classification code: M6 Hazard ID no: 90
Environmentally hazardous substance, Liquid, n.o.s (Epoxy resin)
IMDG/IMO EmS: F-A,S-FIATA/ICAO Packing Instructions: 914 Tariff Number: 39073000

**SECTION 15**

Regulatory references:

REGULATORY INFORMATION

Regulations (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation EU 453/2010 amending Regulation (EC) No 1907/2006.

**SECTION 16****OTHER INFORMATION**

N.B. This SDS gives a summary of the product's classification and hazards under the CLP Regulations, the full version is available from the office.
Always use in accordance with manufacturer's directions. Dated 01/02/15 CLP/Rev.1

TERO TECH Merchant House, Parsonage Square, Dorking, Surrey RH4 1UP. Tel: 01827 283322 Fax: 01827250143

TERO TECH is a wholly owned subsidiary of the IM Group

The IM Group utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. Apply protective coatings per company standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. Trademark(s): **TERO TECH** is a registered trademark of the IM Group.

