TERO TECH™ Better Building Maintenance Products

IMG INDUSTRIALMAINTENANCEGROUP

Inter Active Primer

Advanced self-leveling expansion joint sealant primer

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assesments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.

SECTION 1 PRODUCT IDENTIFICATION

Product name	Inter Active Primer
Product use	Component of expansion joint filling system.

SECTION 2 HAZARDS IDENTIFICATION

Classification 1272/2008/EC	Physical and Chemical Hazards	Not classified
	Human health	Asp.Tox.1; H304; Sk.Irrit.2; H315; Sk. Sens.1; H317; Eye Irrit.2; H319; Acute Tox.4; H332; Resp.Sens.1; H334; STOT SE3; H335; Carc. 2; H351; STOT RE2; H373
	Environment	Aq.Chron.2; H411
Hazard symbols:	Signal word: Danger	Contains: Aromatic polyisocyanate prepolymer; Low Boiling Point Naphtha-Unspecified-Solvent Naphtha (Petroleum) Light Arom.

Hazard statements:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long-lasting effects

Precautionary statements:

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+352	IF ON SKIN: Wash with plenty of water
P333+313	If skin irritation or a rash occurs: Get medical advice/attention.
P304+340	IF INHALED: Remove person to fresh air and keep comfortable for breathing
P342+311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+313	If exposed or concerned: Get medical advice/attention.
P501	Dispose of contents/container in accordance with national regulations.

Supplemental label information:

EUH204	Contains Isocyanates. May produce an allergic reaction.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components **Related Information**

Chemical Name(s)	% (w/w)	CAS no.	Classification / H Statements
Aromatic polyisocyanate prepolymer	50-70	-	Sk. Irrit. 2; H315; Sk.Sens.1; H317; Eye Irrit. 2; H319; Ac.Tox.4; H332; Resp. Sens. 1; H334; STOT SE 3; H335;

Skin: Wash with soap and water and seek medical advice.

Low Boiling Point Naphtha-Unspecified-Solvent Naphtha (Petroleum) Light Arom.	30-50	64742-95-6	Flam.Liq.3; H226; Asp.Tox.1; H304; STOT SE3; H335; Muta 1B; H340; Carc.1B; H350; Aq.Chron.2; H411

SECTION 4 FIRST AID MEASURES

Contact with	
Eyes	Flush with water for 15 minutes. Seek immediate medical advice.
Ingestion	Wash out mouth with water. Do not induce vomiting. Give water to drink. Seek medical advice.
Inhalation	Remove to fresh air. Seek medical advice.
Skin	Wash with soap and water and seek medical advice.

SECTION 5 FIRE FIGHTING MEASURES

Extinguishing media	Carbon dioxide, dry powder, alcohol resistant foam.
Special procedures	Wear protective clothing to prevent contact with skin and eyes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Clean-up procedures: Do not discharge into drains or rivers. Absorb with sand/earth and transfer to a labelled salvage container.

SECTION 7 HANDLING AND STORAGE

Handling	Avoid contact with skin and eyes. Wash hands after use and before meal breaks.
Storage	Store in original containers in a cool, well ventilated area between 10°C and 35°C. Keep containers tightly closed.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Hazardous components	Workplace exposure limits (WELs)		
Chemical name	8 hour TWA	15 min STEL	Related information
Isocyanates (as -NCO)	0.02 mg m-3	0.07 mg m-3	(Sen - capable of causing occupational asthma.)
Engineering measures	Ensure there is sufficient ventilation of the area. Do not handle in a confined space.		
Respiratory protection	If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required, in which case, use gas mask fitted with filter type A.		
Hand protection	Protective gloves.		
Eye protection	Wear safety glasses if there is a risk of eye contact.		
Skin protection	Protective overalls.		

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

State: Non-viscous liquid | Odour: Aromatic | Solubility in water: Insoluble | Colour: Yellow

Flash Point (°C): 23-60

SECTION 10 STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	Excessive heat for prolonged periods.
Materials to avoid	Strong oxidising agents. Strong acids.
Decomposition products	Toxic fumes may be emitted in fire conditions.

SECTION 11 TOXICOLOGICAL INFORMATION

Hazardous ingredients: Low Boiling Point Naphtha-Unspecified-Solvent Naphtha (Petroleum) Light Arom.

ORL RAT LD50 8400mg/kg

Skin	Irritation to skin, may cause sensitisation. May cause an allergic skin reaction.
Eye	May cause irritation.
Ingestion	Can cause irritation to mouth, throat or stomach.
Inhalation	Vapours or fumes may irritate mucous membranes.

SECTION 12 ECOLOGICAL INFORMATION

Should not be discharged directly in concentrated form to water courses. Toxic to aquatic life with long-lasting effects.

SECTION 13 DISPOSAL CONDITIONS

Disposal operations: Contact licensed waste disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14 TRANSPORT INFORMATION

UN no: 1263 Class: 3 PG: III Labelling: 3 ADR/RID Classification code: F1 Hazard ID no: 33
Shipping name: Paint related material(Solvent Naphtha Light Aromatic C9, Aromatic Polyisocyanate Prepolymer)
IMDG/IMO EmS: F-E,S-E Marine Pollutant: No IATA: UN1263 PG III Tariff Number: 35069900

SECTION 15 REGULATORY INFORMATION

Regulatory references: Regulations (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation EU 453/2010 amending Regulation (EC) No 1907/2006.

SECTION 16 OTHER INFORMATION

N.B. This SDS gives a summary of the product's classification and hazards under the CLP Regulations, the full version is available from the office.
Always use in accordance with manufacturer's directions.
Dated 07/08/17 CLP/Rev.1

TERO TECH Merchant House, Parsonage Square, Dorking, Surrey RH4 1UP. Tel: 01827 283322 Fax: 01827250143
TERO TECH is a wholly owned subsidiary of the IM Group

The IM Group utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. Apply protective coatings per company standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. Trademark(s): **TERO TECH** is a registered trademark of the IM Group.