

ROCKFLOW

Ultra tough floor repair and screeding product



Repair large, uneven floor surfaces without the need for trowel finishing.

What is Rockflow?

Rockflow's unique, rapid-curing, formulation can be used on a variety of building materials. Rockflow is easy to apply and will even self-level to save you time. The ultra-tough finish of Rockflow will withstand even heavy duty fork lift traffic.

How does Rockflow work?

Rockflow uses a unique mix of polymers and fillers that won't shrink and which cures to an ultra-tough finish.

Key features and benefits of Rockflow

Easy to use formulation just add water.

Can be laid at depths of 2mm to 50mm.

Cures rapidly – area is usable after 2 hours.

Use on damaged and uneven floors – Rockflow will self-level.

Ultra tough and durable – can be used for high traffic areas.

Tools can be washed off with water.

Use on a range of materials such as sand, concrete, asphalt and cement.

Covers large or small areas.

Technical Information

Usable Life: Up to 30 minutes after mixing. Time to foot traffic: 20 hours at 20°C

Application thickness: 2mm to 50mm

Coverage: 4.8 square metres at 3mm.

Compressive strength:

28 days: 40.0 Newtons per sq mm

7 days: 35.0 Newtons per sq mm

1 day: 25.0 Newtons per sq mm

Flexural strength: 28 days: 9.7 Newtons per sq mm

7 days: 5.0 Newtons per sq mm

1 day: 3.5 Newtons per sq mm

Primer: Rockflow Universal Primer

Coverage of 20 square metres per litre

Recommended for use with: Rockflow, Universal Primer, Easi-Floor.

Always ensure that precautionary measures found in the MSDS sheet for Rockflow are read and followed before use.

TEROTECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECHTECH** is a registered trademark and subsidiary of **IM Group**.

