



Storm Seal

Easy to apply rapid response roof waterproofing



What is Storm Seal?

Storm Seal is a bitumen solution that can be quickly and easily sprayed on to any kind of roofing material to produce a thick, instantly waterproof seal even in emergency conditions. No heating, brushing or trowelling is needed – just aim and spray! It can even be used to repair worn or leaky gutters and rainwater outlet systems, or used as a waterproof undercoating.

How does Storm Seal work?

Storm Seal is a unique foaming bitumen solution that can be applied to virtually any roofing surface in temperatures from -5oC up to 40oC, without special tools or training. It achieves a high build rapidly and adheres even to lead and other metals securely.

Key features and benefits of Storm Seal

Just point and spray, so ideal for areas where access is difficult. Expands rapidly after spraying, achieving a high build quickly. No heating, brushing or trowelling.

Can be applied in virtually any temperature.

Can be used with reinforcement sheets to strengthen weak areas. Instantly waterproof.

Goes on quickly and evenly in one pass.

Areas of Use

Storm Seal can be applied quickly to provide emergency waterproofing or waterproofing reinforcement to almost any roofing material, including felt, asphalt, slate, tile, profiled sheet, cement, concrete, lead and other metals. Can be used as an effective waterproof underseal for metal surfaces including gutters and rain spouts.

For your protection, always read the MSDS sheet for Storm Seal before use and follow it closely.

TERO TECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW. Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031



