

# Stormseal

Page 1 of 8  
Issued: 04/04/2019; Revision No.2  
Regulation (EC) No.453/2010

## 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### 1.1 Product Identifier

Material name : Stormseal

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Spray-on roof repair coating.

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: IMG Ltd.,  
Unit M  
Riverside Industrial Estate  
Fazeley  
Tamworth  
B78 3RW

Tel. : 01827 283322  
Fax. : 01827 250143

Email (for SDSs) : sales@img-limited.co.uk

1.4 Emergency tel. no.: 01827 283322 (Available from 8.30 – 17.00 hours).

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

According to 1272/2008/EC: Classification, Labelling and Packaging of Substances and Mixtures (CLP) Regulation:

Physical and Chemical Hazards	Flam.Aerosol 1; H222; H229
Human health	STOT SE3; H336
Environment	Aq.Chron. 2; H411

### 2.2 Label elements

Labelling according to EC Directives: 1272/2008/EC

Signal word: Danger

Contains: White Spirit

Pictogram(s):



<b>Hazard Statements:</b>	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
	H336	May cause drowsiness or dizziness.
	H411	Toxic to aquatic life with long lasting effects.

<b>Precautionary Statements:</b>	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C.
	P261	Avoid breathing vapour/spray.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves/eye protection/face protection

# Stormseal

Page 2 of 8  
Issued: 04/04/2019; Revision No.2  
Regulation (EC) No.453/2010

## Precautionary

**Statements (continued):** P314 Get medical advice/attention if you feel unwell.  
P501 Dispose of contents/container in accordance with local/national regulations.

**2.3 Other hazards** In use, may form flammable / explosive vapour-air mixture.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures:

#### Hazardous components

Chemical Name	CAS No./ EC No./ Reg. No	Classification (1272/2008/EC)	Content
OXIDISED ASPHALT (Bitumen)	64742-93-4 - 01-2119498270-36-0004	Not classified but has a WEL, see Section 8	25-50%
WHITE SPIRIT	64742-82-1 919-446-0 01-2119458049-33-xxxx	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336i Aquatic Chronic 2; H411	10-30%
LIQUEFIED PETROLEUM GAS (contains <0.1% 1,3-butadiene)	68476-85-7 270-704-2 -	Flam.Gas 1; H220 Gas under pressure; H280	10-30%
DIMETHYL ETHER	115-10-6 204-065-8 01-2119472128-27-0000	Flam.Gas 1; H220 Gas under pressure; H280	10-30%

See Section 16 for the full text of the H-statements noted above.

(1272/2008/EC: Classification, Labelling and Packaging of Substances and Mixtures (CLP) Regulation).

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

**General advice:** Remove casualty from exposure ensuring one's own safety whilst doing so. Take off any contaminated clothing and shoes/boots immediately. Never give anything by mouth to an unconscious person.

**Skin contact:** Wash with soap and water. Seek medical advice if irritation develops.

**Eye contact:** Rinse with water for 10 minutes and seek medical advice if irritation persists.

**Ingestion:** Rinse mouth with water and give water to drink. Do not induce vomiting. Seek medical advice.

**Inhalation:** Remove to fresh air. Seek medical advice.

**4.2 Most important symptoms and effects, both acute and delayed:** May cause irritation to skin and eyes with prolonged contact.

**4.3 Indication of any immediate medical attention and special treatment needed:** See skin and eye contact information above.

## 5. FIRE-FIGHTING MEASURES

### 5.1 Extinguishing media

Suitable extinguishing media: Carbon dioxide; dry chemical powder; alcohol or polymer foam.

Unsuitable extinguishing media: High volume water jet

# Stormseal

Page 3 of 8  
Issued: 04/04/2019; Revision No.2  
Regulation (EC) No.453/2010

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Irritating/toxic fumes may be released at elevated temperatures.

## 5.3 Advice for fire-fighters:

Special protective equipment: Wear self-contained breathing apparatus. Use personal protective equipment.

Further information: Standard procedure for chemical fires. Use water spray to cool containers.  
Do not allow fire run-off to enter drains.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Use personal protective equipment to deal with spillage.

### 6.2 Environmental precautions

Contain the spillage using sufficient appropriate absorbent material. Do not discharge into drains or rivers, but if contamination to waterways has occurred, inform local authorities.

### 6.3 Methods and materials for containment and cleaning up

Wipe up liquid spillage with absorbent material such as sand, earth, or vermiculite, and place in a labelled container for disposal in accordance with local/national regulations.

**6.4 References to other sections:** See sections 8 and 13 for personal protection and disposal information.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Do not breathe spray mist. Avoid contact with skin and eyes. Handle with care.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, well ventilated area, below 50°C. Protect from frost, heat and sunlight. Incompatible with oxidising agents. Keep away from food, drink and animal feed.

**7.3 Specific end use(s):** No information available.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

Chemical name	8hr TWA	15min STEL	Reference
Oxidised asphalt, petroleum fumes	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	EH40/2005
White spirit	1200 mg/m <sup>3</sup>	-	Manufacturer
Liquefied petroleum gas	1750 mg/m <sup>3</sup> /1000ppm	2810 mg/m <sup>3</sup> /1250 ppm	EH40/2005
Dimethyl ether	766 mg/m <sup>3</sup> /400ppm	958 mg/m <sup>3</sup> /500 ppm	EH40/2005

# Stormseal

## DNEL:

DNEL (workers)	White spirit	Reference
Chronic systemic effects (inhalation)	330 mg/m <sup>3</sup>	Manufacturer
Chronic systemic effects (dermal)	44 mg/kg bw/day	Manufacturer

DNEL (consumers)	White spirit	Reference
Chronic systemic effects (inhalation)	71 mg/m <sup>3</sup>	Manufacturer
Chronic systemic effects (dermal)	26 mg/kg bw/day	Manufacturer

**PNEC:** The solvent is a hydrocarbon with a complex, unknown or variable composition (UVCB). Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.

## 8.2 Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

### Personal protective equipment

**Respiratory protection:** If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required, in which case use respirators fitted with organic vapour filters.

**Hand protection:** Chemically-resistant gloves; check with glove manufacturer for specific advice.

**Eye protection:** Tightly-fitting safety goggles.

**Skin and body protection:** Protective overalls.

**Hygiene measures:** Handle in accordance with good industrial hygiene and safety practices. Do not eat or drink whilst using the product. Wash hands before breaks and at the end of the work day. Wash contaminated clothing before re-use.

**Environmental exposure controls:** Do not discharge into drains or rivers.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

State and colour	Aerosol emitting black oily spray
Odour	Characteristic
Odour Threshold	No data available
Flammability	Extremely flammable
Flash point	-40°C
Lower explosion limit	0.8%
Upper explosion limit	9.0%
Explosive properties	Not explosive
Thermal decomposition	No data available
Auto-ignition temperature	No data available
Oxidising properties	Non-oxidising
Solubility in water	Insoluble
Solubility in other solvents	Soluble in most organic solvents
pH	Not applicable
Melting point/range	No data available
Boiling point/range	No data available
Relative density	0.85 @ 20°C (liquid material)
Vapour pressure	No data available
Vapour density	No data available

# Stormseal

## 9.1 Information on basic physical and chemical properties (continued)

Partition coefficient: n-octanol/water	No data available
Viscosity (kinematic)	Slightly viscous (liquid material)
Evaporation rate	No data available

9.2 Other information No data available

## 10. STABILITY AND REACTIVITY

10.1 Reactivity	Generally non-reactive.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	None if stored and used as directed.
10.4 Conditions to avoid	None known.
10.5 Incompatible materials	Strong oxidising agents. Strong alkalis.
10.6 Hazardous decomposition products	Oxides of carbon.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Acute toxicity

Chemical name	Oral (LD50)	Inhalation (LC50)	Dermal (LD50)
Oxidised asphalt	>5000 mg/kg (Rat)	No data	>2000 mg/kg (Rabbit)
White spirit	>15000 mg/kg (Rat)	>1.58 mg/l (Rat) 4h	>3400 mg/kg (Rabbit)
Liquefied petroleum gas	Not applicable	>20mg/l (Rat) 4h	Not applicable
Dimethyl ether	Not applicable	164000 ppm (Rat)	Not applicable

**Skin corrosion/irritation:** Oxidised asphalt: Expected to be slightly irritating.  
White Spirit: Defatting to skin. May cause skin dryness and irritation.

**Serious eye damage/eye irritation:** Oxidised asphalt: Expected to be slightly irritating.  
White Spirit: No known significant effects or critical hazards.

**Respiratory or skin sensitisation:** Oxidised asphalt: Not expected to be a sensitiser.  
White Spirit: Not classed as a respiratory or skin sensitiser.

**Repeated dose toxicity:** No data available

**Carcinogenicity:** Oxidised asphalt: No carcinogenicity classification, however bitumens contain low amounts of polycyclic aromatic compounds (PACs). When diluted it is believed that these compounds become bioavailable, and may pose a health risk but there is no absolute data on the effects in humans.

**Mutagenicity:** No data available

**Toxicity for reproduction:** No data available

**Specific target organ toxicity (STOT):** Oxidised asphalt: Not expected to be a hazard.  
White Spirit: Narcotic effects.

**Further information** The product as a whole may cause irritation of skin, eyes, nose and upper respiratory tract if exposed to high levels of spray mist.

# Stormseal

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

Chemical name	Species	Test	Value
Oxidised asphalt	Daphnia	LL/EL/IL50	>100 mg/l
	Fish	LL/EL/IL50	>100 mg/l
	Algae	LL/EL/IL50	>100 mg/l
White spirit	Daphnia	EC50 48h	10-20 mg/l
	Rainbow trout	EC50 96h	10-30 mg/l
	Algae	EC50 72h	4.6-10 mg/l

### 12.2 Persistence and degradability

Oxidised asphalt: Not expected to be readily biodegradable.

### 12.3 Bioaccumulative potential

Oxidised asphalt: Has the potential to bioaccumulate.

### 12.4 Mobility in soil

The product is slightly soluble in water and will partially migrate through and partially adsorb to soil.

### 12.5 Results of PBT and vPvB assessment

Contains no PBT or vPvB substances.

### 12.6 Other adverse effects

Toxic to aquatic life with long-lasting effects.

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Disposal operations: Dispose of in accordance with local and national regulations.  
Contact licensed waste disposal company. Most aerosols can be recycled.  
Do not pierce or burn or use a cutting torch on the empty aerosol container.

## 14. TRANSPORT INFORMATION

General Information: The UN number for all aerosols is 1950. Aerosols packed in fibreboard cartons up to 30 kg gross weight, or shrink/stretch wrapped onto trays up to 20 kg gross weight may be transported as Limited Quantities, and should display the following symbol on the pack:



The following information relates to all other aerosols not transported as Limited Quantities:

**14.1 UN number**                      ADR/RID/ADN; IMDG; ICAO    1950

**14.2 UN proper shipping name**    AEROSOLS

# Stormseal

Page 7 of 8  
Issued: 04/04/2019; Revision No.2  
Regulation (EC) No.453/2010

<b>14.3 Transport hazard class(es)</b>	ADR/RID/ADN Class	2, 5F
	ADR/RID/ADN Class	Class 2, Gases
	ADR Label No.	2.1
	IMDG Class	2
	ICAO Class/Division	2
	ICAO Subsidiary risk	2.1



Transport labels

**14.4 Packing Group** ADR/RID/ADN; IMDG; ICAO Not applicable for aerosols

**14.5 Environment hazards** Marine Pollutant Not applicable for aerosols.

**14.6 Special precautions for user** EMS F-D,S-U  
Tunnel restriction code (D)

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable for aerosols.

## 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### UK Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2001 No.2677) with amendments.

#### EU Directives

Regulations (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

#### Statutory Instruments

The Chemicals (Hazard information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

#### Guidance Notes

Health and Safety Executive Workplace Exposure Limits EH40.

Volatile Organic Compounds (VOC) content: 850 g/l. (Directive 1999/13/EC)

### 15.2 Chemical Safety Assessment

Chemical Safety Assessments/Reports (CSA/CSR) are not required for mixtures.

## 16. OTHER INFORMATION

This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006 (REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals).

Tariff number: 27150000

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 (CLP):

Physical hazards: On basis of test data/Expert judgement.  
Health hazards: Calculation method  
Environmental hazards: Calculation method

# Stormseal

Page 8 of 8  
Issued: 04/04/2019; Revision No.2  
Regulation (EC) No.453/2010

## Full text of H-statements referred to under sections 2 and 3

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure, may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336i	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects

## Abbreviations and acronyms

Asp: Aspiration (Section 3).  
CAS: Chemical Abstract Service (division of the American Chemical Society). {Section 3}.  
STOT: Single Target Organ Toxicity (Section 3 and 11).  
TWA: Time-weighted average. (Section 8).  
STEL: Short-term exposure limit. (Section 8).  
DNEL: Derived no effect level – a level above which humans should not be exposed. (Section 8).  
PBT: Persistent, Bioaccumulative, Toxic. (Section 12).  
vPvB: very Persistent and very Bioaccumulative. (Section 12).  
EC50: Effective Concentration, 50 percent. (Section 12).  
IC50: Inhibition Concentration, 50 percent. (Section 12).  
LC50: Lethal Concentration, 50 percent. (Section 11/12).  
LD50: Lethal Dose, 50 percent. (Section 11).

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]

