



# Supercover

## Roof coating

In compliance with Chip 4 and ACOP, Compilation of Data Sheets 4th Edition, this information is provided to help inform Risk Assessments. Its contents cannot be considered to be a risk assessment under Management of Health and Safety or other such regulations. Risk assessments require consideration of other information related to the precise circumstances and situation or preparation to be used. Such information is not available to the supplier/compiler of this data.

**SECTION 1**

Product name  
Product use

**PRODUCT IDENTIFICATION**

Supercover  
Roof repair compound.

**SECTION 2**

Classification 1272/2008/EC

**HAZARDS IDENTIFICATION**

Physical and Chemical Hazards  
Human health  
Environment  
Contains: White Spirit; Xylene

Flam. Liq. 3, H226  
Acute Tox.4; H312+332; Sk.Irrit.2; H315; STOT RE2, H373  
Aquatic Chronic 2, H411



Signal word: Warning  
Hazard symbols:  
Hazard statements:



Precautionary statements:

H226 Flammable liquid and vapour.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation  
H332 Harmful if inhaled.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long-lasting effects

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection  
P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P370+378 In case of fire: Use foam, CO2, dry powder, water fog to extinguish.  
P403+235 Store in a well ventilated place. Keep cool.  
P501 Dispose of contents/container in accordance with national regulations.  
EUH066 Repeated exposure may cause skin dryness or cracking.

Supplemental labelling information

**SECTION 3**

**Hazardous components**  
**Chemical Name(s)**

White Spirit  
Xylene

**COMPOSITION/INFORMATION ON INGREDIENTS**

**Related Information**

% (w/w)	CAS no.	Classification/H-Statements
25-50	64742-88-7	Flam. Liq. 3, H226; STOT RE1, H372; Asp.Tox.1, H304; Aq.Chron.2, H411
10-30	1330-20-7	Flam. Liq. 3, H226; Acute Tox. 4, H312, H332; Skin Irrit. 2, H315

**SECTION 4**

In cases of contact  
Eyes  
Ingestion  
Inhalation  
Skin

**FIRST AID MEASURES**

Flush with water for 15 minutes. Seek medical advice if irritation persists.  
Do not induce vomiting. Give water to drink. Seek immediate medical advice and show this sheet.  
Remove to fresh air for at least 10 minutes.  
Wash skin thoroughly with soap and warm water. Dry skin and apply replenishing cream.  
Seek medical advice if irritation develops.

**SECTION 5**

Extinguishing media  
Special procedures

**FIRE FIGHTING MEASURES**

Use Carbon Dioxide, dry powder, foam or water spray. Do not use water jet.  
Wear self-contained breathing apparatus for chemical fires. Use water spray to keep containers cool and vapours down.

**SECTION 6**

Clean-up procedures

**ACCIDENTAL RELEASE MEASURES**

Remove all ignition sources. Do not discharge into drains or rivers. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**SECTION 7**Handling  
Storage**HANDLING AND STORAGE**

Do not eat, smoke or drink whilst working with this material. Wash hands before meals and after work. Store in a cool, well ventilated area. Keep containers tightly closed.

**SECTION 8**

Hazardous components  
Chemical name  
White Spirit  
Xylene  
Engineering measures  
Respiratory protection  
Hand protection  
Eye protection  
Skin protection

**EXPOSURE CONTROLS AND PERSONAL PROTECTION**

Workplace exposure limits (WELs)  
8 hour TWA  
15 min STEL  
Related information  
(Supplier's classification)  
100 ppm  
220 mg/m<sup>3</sup> 441 mg/m<sup>3</sup> (Sk)  
Ensure there is sufficient ventilation of the area.  
If Workplace Exposure Limit(s) listed above are exceeded, respiratory protection may be required.  
Protective gloves. (Sk) means can be absorbed through skin.  
Wear safety glasses if there is a risk of eye contact.  
Protective overalls.

**SECTION 9**State: Viscous liquid  
Colour: Black**PHYSICAL AND CHEMICAL PROPERTIES**

Odour: Characteristic  
Flash point °C: 38  
Solubility in water: Insoluble  
Flammability limits: 0.9% – 8.0%  
S.G. 1.03

**SECTION 10**

Stability  
Conditions to avoid  
Materials to avoid  
Decomposition products

**STABILITY AND REACTIVITY**

Stable under normal conditions.  
Hot surfaces. Sources of ignition. Flames.  
Strong oxidising agents. Strong acids. Strong bases.  
Combustion will generate oxides of carbon, acrid smoke and irritating fumes.

**SECTION 11**

Hazardous ingredients:  
  
Routes of exposure:

**TOXICOLOGICAL INFORMATION**

Xylene  
ORL MUS LD50 2119 mg/kg, ORL RAT LD50 4300 mg/kg, SCU RAT LD50 1700 mg/kg  
Exposure to high levels of vapour may cause drowsiness, dizziness, nausea, headaches, vomiting.  
Prolonged contact with skin may cause irritation leading to dermatitis in extreme cases.  
Small amounts of liquid aspirated into respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

**SECTION 12****ECOLOGICAL INFORMATION**

Should not be discharged directly in concentrated form to water courses. Toxic to aquatic organisms.

**SECTION 13**

Disposal operations

**DISPOSAL CONDITIONS**

Contact licensed waste disposal company.  
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**SECTION 14**

UN no: 1993  
Shipping name:

**TRANSPORT INFORMATION**

Class: 3 PG: III Labelling: 3 ADR/RID Classification code: F1 Hazard ID no: 30  
Flammable Liquid, n.o.s. (White Spirit) IMDG/IMO EmS: F-E,S-E\*  
IATA/ICAO Packing Instructions: 309 (P&CA); 310 (CAO) Tariff Number: 27150000

**SECTION 15**

Regulatory references:

**REGULATORY INFORMATION**

Regulations (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation EU 453/2010 amending Regulation (EC) No 1907/2006.

**SECTION 16****OTHER INFORMATION**

N.B. This SDS gives a summary of the product's classification and hazards under the CLP Regulations, the full version is available from the office.  
Always use in accordance with manufacturer's directions. Dated 21/08/2017 CLP/Rev.1

**TERO TECH** Merchant House, Parsonage Square, Dorking, Surrey RH4 1UP. Tel: 01827 283322 Fax: 01827250143

**TERO TECH** is a wholly owned subsidiary of the IM Group

The IM Group utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. Apply protective coatings per company standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. Trademark(s): **TERO TECH** is a registered trademark of the IM Group.

