

Superflex High Build

A self-reinforced patching compound



A self-reinforced patching compound for long lasting roof repairs

What is Superflex High Build?

Superflex High Build is a flexible waterproof barrier that can be applied to virtually any roofing material, wet or dry, to repair leaks and cracks. It even works for large scale patching and making extensive repairs. It can be used right from the tin with no mixing, and can be applied with a brush, trowel or roller. Its advanced chemistry allows repairs to last up to ten years.

How does Superflex High Build work?

Superflex High Build is a self-reinforced, long lasting acrylic polymer. This bonds well to any common roofing and construction materials, including felt, asbestos, concrete, lead, iron and other metals, asphalt and even glass.

Its high-build nature allows even extensive repairs to be made quickly and easily.

Key features and benefits of Superflex High Build

- Fast and easy to use – no mixing and no priming required
- Contains self-reinforcing fibres for added support and long lasting repairs
- Can be applied to wet or dry surfaces
- Bonds to virtually any construction material
- Choice of two colours:
 - Highly reflective white surface keeps buildings cool and reduces energy use
 - Black option absorbs solar radiation, blending in with common roofing materials and reducing the accumulation of snow and ice
- Forms a flexible barrier that prevents further cracking
- Long shelf-life in the tin, even after opening

Technical Information

Superflex High Build is touch-dry approximately 4 hours after application, and can withstand foot traffic after 24 hours. Wait at least 16 hours before overcoating. The coverage is approximately 1 square metre per kilo, depending on the type of surface to be covered. Available in white and black.

Use with fibreglass matting to span larger gaps and holes. Overcoat with Superflex Smooth for an even more attractive and durable finish.

For your protection, always read the MSDS sheet for Superflex High Build before use and follow it closely.

TEROTECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECHTECH** is a registered trademark and subsidiary of **IM Group**.

