



FLEXI-SEAL



Self Amalgamating Tape



Flexi - Seal - The fast easy way to sealing solutions

What is Flexi-Seal?

Wires, pipes or tubes may need sealing or fastening together quickly, without any equipment. Ordinary adhesive tapes can be fiddly to use, and come loose when the adhesive weakens. Flexi-Seal is the fast easy solution to give a waterproof, electrically resistant and long lasting repair.

How does Flex-Seal work?

Flexi-Seal tape is made from polyisobutylene, which when stretched and wrapped over itself, bonds together without the need of any heat or chemicals. The product then forms a seamless, waterproof, weather proof finish.

Key Features and Benefits of Flexi-Seal

Flexi-Seal can be used for a wide range of uses including sealing weeping plastic and metal pipes and joints, waterproofing wires, power cables, repairing damaged wires and electrical connections, sealing metal surfaces against corrosion as well as jointing cables together. Can be used underwater, and protects against sea water.

Flexi-Seal Technical information

Dielectric Strength: Approx. 14000 volts per layer

Tensile Strength: 2 mpa (BS903)

Elongation to break: 900% (BS903)

Storage life: 5 years at + 10°C to +30°C

Operating temperature: minus 40°C to + 90°C

10 + 90 (

Note- not suitable to protect against oils and petroleum compounds.

Metalyte Riverside Ind. Estate Fazeley, Tamworth Staffordshire B78 3RW

Telephone: 01827 283322 Fax: 01827250143 Metalyte Pipeworks is a wholly owned subsidiary of the IM Group

