



CDT FLUID



Helps Drills, Taps, Metal saws and Dies cut easily and cleanly



What is CDT Fluid?

CDT Fluid is a blend of Fatty Esters and extreme pressure lubricants in solvent refined mineral oils. It can be used on cutting tools, broaches, taps, dies and other extreme pressure tools. It will reduce frictional heat and helps prevent scoring and give you an improved surface finish, even when tapping the toughest of alloys.

It will make drilling and cutting much easier and increases the life of the bit, blade or tool.



CDT Fluid comes in an aerosol making it easy to use and a handy product to have around. It can be used in fitting shops, engineering workshops and all maintenance departments.

CDT Fluid is suitable for use on a wide range of materials including steel, titanium, nimonics, wasp alloy and aluminium, It is also suitable for severe applications on heavy duty alloys.

Key Features and Benefits of CDT Fluid

Contains no lead, graphite or minerals
Helps drills, dies and taps cut easily and cleanly
Cools and lubricates
Extends tools life
Reduces friction

Improved surface finish

Directions For Use

Shake can thoroughly and spray directly onto the surface. Re-apply as required.

Health and Safety

Always ensure that precautionary measures found in the MSDS sheet for CDT Fluid are read and followed before use and please ensure that appropriate PPE is used when preparing, mixing and applying products.



Metalyte Riverside Ind. Estate Fazeley, Tamworth Staffordshire B78 3RW

Telephone: 01827 283322 Fax: 01827250143 Metalyte Pipeworks is a wholly owned subsidiary of the IM Group

