

EASI-FLOOR

Convenient, single pack floor coating



Convenient, single pack floor coating with the superior performance of two-pack epoxies

What is Easi-Floor?

Easi-Floor is a simple to use, single pack floor coating. Easi-Floor is available in a range of colours and can be used on any surface. You can even use Easi-Floor as a sealant for concrete or varnish for wooden floor surfaces.

How does Easi-Floor work?

The innovative Epoxy-Ester based formulation of Easi-Floor means the convenience of a single pack combined with the superior, hardwearing performance associated with two-pack floor coatings.

Key Features and Benefits of Easi-Floor?

Tough and hard wearing Easi-Floor has excellent durability.

Convenient single pack means no mixing.

Easi-Floor can be used on almost any surface.

Use Easi-Floor to coat previously painted surfaces without costly removal of existing coatings.

Touch dry in 3 hours @ 20°C.

Accepts foot traffic after overnight drying for a quick return to service.

Available in a variety of colours.

Multi-purpose product – can be used for sealing concrete or varnishing wooden floors.

TERO TECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031


The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECH TECH** is a registered trademark and subsidiary of **IM Group**.

Issue Date: 10.05.21

Revision Date: 06.06.24

Revision: 2.0



Instructions of Use

Paint preparation: Mix paint thoroughly by stirring continuously to ensure an even consistency.

Surface preparation: All surfaces to be coated should be clean, dry and free from contamination.

Previously primed floors: Ensure existing coating is firm and sound with good adhesion. Thoroughly clean with detergent water, rinse and dry off.

New Concrete: Concrete should be clean, dry and free of surface laitance.

It is recommended that this product is applied in thin layers, each left to dry before applying another on top.

Application conditions

Easi-Floor should preferably be applied at temperatures in excess of 10°C. Relative humidity should not exceed 90%. Good ventilation is essential. Substrate temperature should be at least 3°C above the dew point and always above 0°C. At application temperatures below 10°C, drying and curing times will be significantly extended.

Brush application: Apply using full wet brush evenly.

Roller application: Apply using a full wet roller evenly.

Health and Safety

Before use, it is important that you have read the Safety Data Sheet in its entirety and the appropriate PPE is worn during use.



EASI-FLOOR

Convenient, single pack floor coating

Technical information

| | |
|------------------------|--|
| Spreading Rate | 8m ² per litre. Dependant on film thickness applied, surface profile, absorption etc. |
| % Volume Solids | 50% calculated from laboratory formulation. |
| Application Conditions | Application should be in temperatures of +10°C. |
| Storage | keep under cover, within temperature range of 5°C to 32°C. |
| Shelf Life | 2 years or longer in unopened containers when stored as directed. |

| Temperature | Touch Dry | Firm Dry | Overcoat |
|-------------|---------------|----------|-----------|
| 5°C | 7 hrs 30 mins | 15 hrs | Overnight |
| 10°C | 6 hrs | 12 hrs | Overnight |
| 15°C | 4 hrs 30 mins | 9 hrs | Overnight |
| 20°C | 3 hrs | 6 hrs | Overnight |

TERO TECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECH TECH** is a registered trademark and subsidiary of **IM Group**.

Issue Date: 10.05.21

Revision Date: 06.06.24

Revision: 2.0

