

Micro Guard

A high performance multi-purpose waterproof membrane



A high performance multi-purpose waterproof membrane coating for exterior and interior use

What is Micro-Guard?

Micro-Guard is a highly durable, micro-porous wall coating that protects substrates from mould, bacteria and fungus.

Micro-Guard is easily maintained and cleaned making it an essential part of any maintenance routine. Use Micro-Guard on both exterior and interior walls, it won't peel and is easy to clean making it ideal for food preparation areas. Micro-Guard is highly durable for exterior use, allowing buildings to breathe while still withstanding high pressure washing systems and resisting impacts.

How does Micro-Guard work?

Micro-Guard's advanced formulation is a combination of high-quality Titanium Dioxides, Iron Oxides and mica fillers enhanced with acrylic resin.

Micro-Guard is non-chalking, non-peeling and thanks to its innovative formulation it maintains superior opacity and colour retention. Unlike conventional wall coatings the molecular structure of Micro-Guard allows substrates to breath while it protects from mould and fungus.

Key Features and Benefits of Micro-Guard?

Unbeatable protection for interior and exterior walls.

High-opacity, decorative coating in a range of colours

Highly-durable while allowing buildings to breathe.

Won't chalk, won't peel and is simple to clean.

Suitable for use in food preparation areas.

Will cover patched rendering and unsightly renovations.

Resists impacts from machinery and high pressure washing systems.

Protects walls from fungus, mould and bacteria.

Won't support vegetation. Resistant to acid and alkali attack. Camouflage cracks with a mixture of silica sand and Micro-Guard.

Technical Information

Colour range: Brilliant White, Cream, Stone, Magnolia, Green, and Grey.

The following Tero Tech products are recommended for use with Micro-Guard:

Fungicidal Wash – For the removal of vegetation.

Substrate Stabiliser – For sealing absorbent and powdery substrates

Ferro-Guard – For protecting rusted ferrous metal.

Tero-Firma Non Porous Substrate Conditioner – For degreasing all metals.

Always ensure that precautionary measures found in the MSDS sheet for Micro-Guard are read and followed before use, and followed before use.

Micro-Guard drying time

Single coat: 2 to 4hrs

Double coat: 6 to 8hrs

Coverage

3 square metres per litre over 2 coats

TERO TECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECH TECH** is a registered trademark and subsidiary of **IM Group**.

