

Simple Stik

A New Technology • Adhesive By The Metre



Conventional adhesives are messy, smelly and uneconomical in use, they require accurate mixing, complicated measuring out and special application equipment – all of this is expensive and wasteful. The increasing impact of health and safety regulations is making the use of solvent based adhesives almost impossible, but the requirement for adhesion to a wide range of materials still exists.

What is Simple Stik?

Simple Stik is a high quality, solventless, pressure sensitive rubber resin adhesive on a roll. It gives aggressive adhesion to a wide range of materials.

How does Simple Stik work?

Simply place Simple Stik onto the surfaces to be bonded and hand pressure is usually sufficient to obtain a powerful adhesion. Ideal bonding substrates are those which are clean, dry, flat, smooth, dust free and non-porous. Low temperatures may increase the risk of condensation, reducing the tack of Simple Stik.

Key features and benefits of Simple Stik

Clean, easy to use alternative to brush on adhesives.

Non-hardening – permanently flexible.

Excellent bond strength.

No curing time required – instant bonding means that there is no waiting for Simple Stik to dry.

Solvent free, therefore no fumes.

Forms a strong waterproof bond.

No priming – quick and easy to use.

Bond to almost all surfaces – wood, metals, plastics, glass, porcelain, ceramic, veneers, fabric and textiles. Not suitable for plasticised PVC.

Bonding lightweight insulation panels.

Mounting lightweight trim.

Fixing of signs, displays, pictures etc.

Simple Stik has been successfully used by joiners, electricians, automotive engineers, model makers, divers, undertakers, carpet layers, builders, roofers, decorators, window-dressers and maintenance professionals in factories, offices, retail outlets, schools, colleges, hospitals and in all types of transportation systems.

Health and Safety

Before use, it is important that you have read the Safety Data Sheet in its entirety and the appropriate PPE is worn during use.

Applications of Simple Stik

Joining of plastic sheeting, filters, damp proof membranes, woven polypropylene matting etc.

Technical information

Temperature resistance once applied -10°C to +60°C

Chemical resistance toxicity Limited resistance to chemicals, petrol and oil

Shelf life Practically indefinite

Adhesion durability 15 years plus

TERO TECH Riverside Industrial Estate, Fazeley, Tamworth, Staffordshire, B78 3RW.
Head Office, Warehousing and Distribution: Tel: 01827 283322, Fax: 01827 250143. Telesales: 01270 611031

The **IM Group** utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group warrants the quality of this product when used according to directions. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement.

Trademarks: **TECH TECH** is a registered trademark and subsidiary of **IM Group**.

Issue Date: 14.01.17

Revision Date: 10.10.24

Revision: 2.0

