

FSG 220

InS H1 certified, high temperature and pressure lubricant for incidental food contact



Grease & Lubes

What is FSG 220?

FSG 220 is a premium quality, synthetic, food grade, polymer enhanced, extreme pressure, complex grease. The complex thickening system gives this product excellent performance across a wide temperature range and excellent adhesion and cohesion properties.

FSG 220 has extreme pressure, anti-wear, anti-corrosion and oxidation inhibiting additives to enhance performance. FSG 220 provides a high degree of load carrying performance and the lube is insoluble in water, resisting water washout.

Where can FSG 220 be used?

FSG 220 is recommended for the lubrication of plain and rolling element bearings, gears, couplings and other applications which require grease lubrication found in food and beverage plants where incidental food contact may occur. E.g. bakeries, dairies, breweries, bottling plants, canneries, animal feed plants, food packaging manufacturing plants and a wide range of other food related areas.

FSG 220 could also be used in the pharmaceutical industry where product could come into contact with pills etc. that are designed to be ingested.

FSG 220 has exceptional water resistance, enabling it to perform particularly well in applications where frequent washing with water or steam causes problems when an inferior grease is used.

FSG 220's purity also enables it to find use in other areas, where a white, odourless, non-toxic lubricant is required, such as the textile industry.

Key features

- Non-toxic
- Odourless
- High temperature performance of -20°C to 220°C
- InS H1 Certified
- Reduces friction and wear

FSG 220

InS Registration Number:	1795435
NLGI Classification:	2
Worked penetration @ 25°C:	280
Drop point °C:	265
Base fluid viscosity @ 40°C cSt:	950
Operating temperature:	-20 – 220°C
Rust Preventative Properties	
DIN 1743:	Pass

How to use

As with all greases used for the first time, check the compatibility with the grease previously used, and if necessary, purge the area to be lubricated prior to application. Store FSG 220 in such a way that will prevent the ingress of water when stored in the open.

Health and Safety

Always ensure that precautionary measures found in the MSDS sheet are read and followed before use and please ensure that appropriate PPE is used when preparing, mixing and applying products.

