



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 7/1/2024 Revision date: 9/23/2024 Supersedes version of: 7/1/2024 Version: 1.1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product form Product name Product code	<ul> <li>Mixture</li> <li>Chill-Eze HB LT Part A</li> <li>ASEPOX100</li> </ul>
1.2. Relevant identified uses of the substa	nce or mixture and uses advised against
Relevant identified uses Main use category Use of the substance/mixture	<ul> <li>Industrial use,Professional use</li> <li>Low-temp curing floor coating, base component</li> </ul>
1.3. Details of the supplier of the safety da	ta sheet
The Industrial Maintenance Group Unit M, Riverside Industrial Estate Fazeley, Tamworth B78 3RW, Staffordshire T 01827 283 322 <u>sales@img-limited.co.uk</u> , <u>www.img-limited.co.uk</u>	
1.4. Emergency telephone number	
Emergency number	: 01827 283 322

## **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture	
Classification according to Regulation (EC) No. 1272/2008	[CLP]
Acute toxicity (inhal.), Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity - Repeated exposure, Category	1 H372
Hazardous to the aquatic environment – Chronic Hazard,	H411
Category 2	
Full text of H- and EUH-statements: see section 16	

#### Adverse physicochemical, human health and environmental effects

Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. Harmful if inhaled. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

Labelling according to Regulation (EC) No. 12	72/2008 [CLP]
Hazard pictograms (CLP)	GHS07 GHS08 GHS09
Signal word (CLP)	: Danger
Contains	: Cristobalite; Epoxy Polymer; Phenol-Formaldehyde Polymer; Alkyl Glycidyl Ether; Titanium Dioxide
Hazard statements (CLP)	<ul> <li>H315 - Causes skin irritation.</li> <li>H317 - May cause an allergic skin reaction.</li> <li>H319 - Causes serious eye irritation.</li> <li>H332 - Harmful if inhaled.</li> </ul>

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

	H351 - Suspected of causing cancer.
	H372 - Causes damage to organs through prolonged or repeated exposure.
	H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P201 - Obtain special instructions before use.
	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264 - Wash hands, forearms and face thoroughly after handling.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
	P308+P313 - IF exposed or concerned: Get medical advice/attention.
	P312 - Call a POISON CENTRE or doctor if you feel unwell.
	P314 - Get medical advice/attention if you feel unwell.
	P321 - Specific treatment (see supplemental first aid instruction on this label). P391 - Collect spillage.
EUH-statements	: EUH205 - Contains epoxy constituents. May produce an allergic reaction.
	EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Extra phrases	: Contains Pine oils.
2.3. Other hazards	

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008
			[CLP]
Cristobalite	CAS-No.: 14464-46-1	≥ 10 – < 30	STOT RE 1, H372
Epoxy Polymer	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119490020- 53	≥ 10 – < 30	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Phenol-Formaldehyde Polymer	CAS-No.: 9003-36-5 EC-No.: 500-006-8	≥ 10 – < 30	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Alkyl Glycidyl Ether	CAS-No.: 68609-97-2 EC-No.: 271-846-8 EC Index-No.: 603-103-00-4	≥ 2 – < 15	Skin Irrit. 2, H315 Skin Sens. 1, H317
Titanium Dioxide	CAS-No.: 13463-67-7 EC-No.: 236-675-5	≥2-<15	Carc. 2, H351
BENZYL ALCOHOL	CAS-No.: 100-51-6 EC-No.: 202-859-9	≥2-<15	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332
Pine oils	CAS-No.: 8002-09-3	< 2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Epoxy Polymer	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119490020- 53	(5 ≤ C ≤ 100) Eye Irrit. 2; H319 (5 ≤ C ≤ 100) Skin Irrit. 2; H315

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and effe	ects, both acute and delayed
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	<ul><li>Water spray. Dry powder. Foam. Carbon dioxide.</li><li>Do not use a heavy water stream.</li></ul>	
5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	<ul> <li>No fire hazard.</li> <li>No direct explosion hazard.</li> <li>Toxic fumes may be released.</li> </ul>	
5.3. Advice for firefighters		
Firefighting instructions Protection during firefighting	<ul> <li>Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.</li> <li>Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.</li> </ul>	

SECTION 6: Accidental release mea	isures
6.1. Personal precautions, protective eq	uipment and emergency procedures
General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

For non-emergency personnel	
Protective equipment Emergency procedures	<ul> <li>Wear recommended personal protective equipment.</li> <li>Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.</li> </ul>
For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
6.2. Environmental precautions	
Avoid release to the environment.	

6.3. Methods and material for containment and cleaning up	
For containment	: Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.
6.4. Reference to other sections	

For further information refer to section 13.

SECTION 7: Handling and storag	e
7.1. Precautions for safe handling	
Additional hazards when processed Precautions for safe handling	<ul> <li>Not expected to present a significant hazard under anticipated conditions of normal use.</li> <li>Obtain special instructions before use. Do not handle until all safety precautions have beer read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.</li> </ul>
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, incl	uding any incompatibilities
Technical measures Storage conditions Packaging materials	<ul> <li>Keep in a cool, well-ventilated place away from heat.</li> <li>Store locked up.</li> <li>Store always product in container of same material as original container.</li> </ul>
7.2 Specific and use(a)	

7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### National occupational exposure and biological limit values

Chill-Eze HB LT Part A	
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (OEL TWA)	4 mg/m³ respirable 10 mg/m³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2. Exposure controls

### Appropriate engineering controls

### Appropriate engineering controls:

Ensure good ventilation of the work station.

### Personal protection equipment

#### Personal protective equipment:

Wear recommended personal protective equipment. Personal protective equipment symbol(s):



### Eye and face protection

**Eye protection:** Wear a face shield

#### **Skin protection**

#### Skin and body protection:

Wear suitable protective clothing

## Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves	Polyvinylchloride (PVC)	6 (> 480 minutes)			

### **Respiratory protection**

Respiratory protection:

## Wear respiratory protection.

Respiratory protection			
Device	Filter type	Condition	Standard
	Gas/vapour filter		

### Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Various colours.
Appearance	: Viscous.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 199 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 60 °C

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Auto-ignition temperature Decomposition temperature	: 315 °C : Not available
pH	: Not available
Viscosity, kinematic	: > 20.5 mm²/s @ 40C
Solubility	: Immiscible with water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 40 Pa @ 20C
Vapour pressure at 50°C	: 2.72 hPa
Density	: 1702.2 kg/m³
Relative density	: 1.702
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

No additional information available

SECTION 10: Stability and reactivity	
10.1. Reactivity	
The product is non-reactive under normal conditions of use, storage and transport.	
10.2. Chemical stability	

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

High temperature. Direct sunlight.

**10.5. Incompatible materials** 

Oxidizing agent. Strong acids. Strong bases.

**10.6. Hazardous decomposition products** 

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information			
11.1. Information on hazard classes as defined	11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity (dermal)	Not classified Not classified Harmful if inhaled.		
Chill-Eze HB LT Part A			
ATE CLP (gases)	4500 ppmv/4h		
ATE CLP (vapours)	11 mg/l/4h		
ATE CLP (dust,mist)	1.5 mg/l/4h		
Epoxy Polymer (25068-38-6)			
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)		
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))		

## Safety Data Sheet

Phenol-Formaldehyde Polymer (9003-36-5)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Titanium Dioxide (13463-67-7)	
LD50 oral rat	<ul> <li>&gt; 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline</li> <li>425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100</li> <li>(Acute Oral Toxicity)</li> </ul>
Pine oils (8002-09-3)	
LD50 oral rat	3200 mg/kg Source: Corporate Solution From Thomson Micromedex
LD50 dermal rabbit	5000 mg/kg Source: Corporate Solution From Thomson Micromedex
Skin corrosion/irritation	: Causes skin irritation.
Titanium Dioxide (13463-67-7)	
рН	7
Serious eye damage/irritation	: Causes serious eye irritation.
Titanium Dioxide (13463-67-7)	
рН	7
Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity	<ul> <li>May cause an allergic skin reaction.</li> <li>Not classified</li> <li>Suspected of causing cancer.</li> </ul>
Epoxy Polymer (25068-38-6)	
NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure Cristobalite (14464-46-1)	: Causes damage to organs through prolonged or repeated exposure.
	Courses damage to ergone through prelenged or reported experience
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Epoxy Polymer (25068-38-6)	
NOAEL (oral, rat, 90 days)	50 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other:japanese MITI guidelines for toxicity testing of chemicals
Phenol-Formaldehyde Polymer (9003-36-5)	
NOAEL (oral, rat, 90 days)	≈ 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Chill-Eze HB LT Part A	
Viscosity, kinematic > 20.5 mm²/s @ 40C	
11.2. Information on other hazards	

No additional information available

SECTION 12: Ecological information	
12.1. Toxicity	
Hazardous to the aquatic environment, short–term : (acute)	Toxic to aquatic life with long lasting effects. Not classified Toxic to aquatic life with long lasting effects.
(chronic)	Toxic to aquate me with long lasting enects.
Epoxy Polymer (25068-38-6)	
LC50 - Fish [1]	1.2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	9.4 mg/l Test organisms (species): Scenedesmus capricornutum
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Phenol-Formaldehyde Polymer (9003-36-5)	
LC50 - Fish [1]	5.7 mg/l Test organisms (species): Leuciscus idus
LC50 - Fish [2]	> 1000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	3.5 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Titanium Dioxide (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Pine oils (8002-09-3)	
LC50 - Fish [1]	18.35 mg/l Source: The ECOTOXicology database
EC50 - Crustacea [1]	24.5 mg/l Source: The ECOTOXicology database
12.2. Persistence and degradability	
Chill-Eze HB LT Part A	
Persistence and degradability	Not rapidly degradable

## Safety Data Sheet

Cristobalite (14464-46-1)	
Persistence and degradability	Not rapidly degradable
Epoxy Polymer (25068-38-6)	
Persistence and degradability	Not rapidly degradable
Phenol-Formaldehyde Polymer (9003-36-5)	
Persistence and degradability	Not rapidly degradable
Alkyl Glycidyl Ether (68609-97-2)	
Persistence and degradability	Not rapidly degradable
Titanium Dioxide (13463-67-7)	
Persistence and degradability	Not rapidly degradable
BENZYL ALCOHOL (100-51-6)	
Persistence and degradability	Not rapidly degradable
Pine oils (8002-09-3)	
Persistence and degradability	Not rapidly degradable
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessment	
No additional information available	
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
No additional information available	

SECTION 13: Disposal consideration	S
13.1. Waste treatment methods	
Regional waste regulation Waste treatment methods Sewage disposal recommendations Product/Packaging disposal recommendations Additional information European List of Waste (LoW, EC 2000/532) HP Code	<ul> <li>Disposal must be done according to official regulations.</li> <li>Dispose of contents/container in accordance with licensed collector's sorting instructions.</li> <li>Disposal must be done according to official regulations.</li> <li>Disposal must be done according to official regulations.</li> <li>Do not re-use empty containers.</li> <li>20 01 27* - paint, inks, adhesives and resins containing dangerous substances</li> <li>HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.</li> <li>HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.</li> <li>HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.</li> <li>HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment</li> </ul>

## Safety Data Sheet

SECTION 14: Transpo				
accordance with ADR / IME	DG / IATA / ADN / RID	ΙΑΤΑ	ADN	RID
I4.1. UN number or ID n				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
4.2. UN proper shippin	g name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer)	Environmentally hazardous substance, liquid, n.o.s. (Contains Epoxy Polymer)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer)
Fransport document descr	iption			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Contains Epoxy Polymer), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer), 9, III
14.3. Transport hazard o	class(es)			
9	9	9	9	9
14.4. Packing group				
		111	111	
14.5. Environmental haz		111	111	
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary informatic				
<b>14.6. Special precaution</b> <b>Overland transport</b> Classification code (ADR) Special provisions (ADR) imited quantities (ADR) Excepted quantities (ADR) Packing instructions (ADR) Special packing provisions (A fixed packing provisions (AD Portable tank and bulk contain Portable tank and bulk contain ADR) Fank code (ADR)	: M6 : 27 : 51 : E1 : P0 DR) : PP DR) : MF ner instructions (ADR) : T4	4, 335, 375, 601 01, IBC03, LP01, R001 1 219 1, TP29		
/ehicle for tank carriage Fransport category (ADR) Special provisions for carriage	: AT : 3			

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

		, , , , , , , , , , , , , , , , , , , ,
Special provisions for carriage - Loading, unloading and handling (ADR)	:	CV13
Hazard identification number (Kemler No.)	:	90
Orange plates	:	00
		90
		3082
		3082
Tunnel restriction code (ADR)	:	-
EAC code	:	•3Z
Transport by sea		
Special provisions (IMDG)	:	274, 335, 969
Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	LP01, P001
Special packing provisions (IMDG)	:	PP1
IBC packing instructions (IMDG)	:	IBC03
Tank instructions (IMDG)	:	Τ4
Tank special provisions (IMDG)	:	TP1, TP29
Stowage category (IMDG)	:	A
Air transport		
PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y964
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	÷	964
PCA max net quantity (IATA)	:	450L
CAO packing instructions (IATA)	÷	964
CAO max net quantity (IATA)	÷	450L
Special provisions (IATA) ERG code (IATA)	:	A97, A158, A197, A215 9L
	•	9L
Inland waterway transport		
Classification code (ADN)	:	M6
Special provisions (ADN)	:	274, 335, 375, 601
Limited quantities (ADN)		5 L
Excepted quantities (ADN)	:	E1
Carriage permitted (ADN)	:	Т
Equipment required (ADN)	:	PP
Number of blue cones/lights (ADN)	:	0
Rail transport		
Classification code (RID)		M6
Special provisions (RID)		274, 335, 375, 601
Limited quantities (RID)		5L
Excepted quantities (RID)		E1
Packing instructions (RID)		P001, IBC03, LP01, R001
Special packing provisions (RID)	-	PP1
Mixed packing provisions (RID)		MP19
Portable tank and bulk container instructions (RID)	:	T4
Portable tank and bulk container special provisions (RID)	:	TP1, TP29
Tank codes for RID tanks (RID)		LGBV
Transport category (RID)		3
Special provisions for carriage – Packages (RID)		W12
Special provisions for carriage - Loading, unloading	:	CW13, CW31
and handling (RID)		050
Colis express (express parcels) (RID)		CE8
Hazard identification number (RID)	:	90

## 14.7. Maritime transport in bulk according to IMO instruments

### Not applicable

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU-Regulations**

### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Chill-Eze HB LT Part A ; Epoxy Polymer ; Phenol- Formaldehyde Polymer ; Alkyl Glycidyl Ether ; BENZYL ALCOHOL	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Chill-Eze HB LT Part A ; Epoxy Polymer ; Phenol- Formaldehyde Polymer ; Pine oils	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### Council Regulation (EC) for the control of dual-use items

Contains substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### **SECTION 16: Other information**

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	

## Safety Data Sheet

Abbreviations and acronyms:		
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
РВТ	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disruptor	

Full text of H- and EUH-statements:		
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Carc. 2	Carcinogenicity, Category 2	
EUH205	Contains epoxy constituents. May produce an allergic reaction.	
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.	

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

9/23/2024 (Revision date)

GB - en Revision: 1.1 14/14

TERO TECH Riverside Ind. Estate, Fazeley, Tamworth, Staffordshire B78 3RW. Tel: 01827 283322 Fax: 01827250143

The IM Group utilizes a process of continuous product improvement for all of our products. While we do strictly adhere to our products' specifications, we routinely implement product improvements. Therefore, please contact us for our most current product specifications. IM Group "arrants the quality of this product when used according to directions. Apply protective coatings per company standards. User shall determine suitability of product for use and assumes all risk. The seller will not accept liability for more than product replacement. Trademark(s): **TERO TECH** is a registered trademark of the IM Group.

