

Chill-Eze HB LT - Part A

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 7/1/2024 Revision date: 9/23/2024 Supersedes version of: 7/1/2024 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Chill-Eze HB LT Part A
Product code : ASEPOX100

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Low-temp curing floor coating, base component

1.3. Details of the supplier of the safety data sheet

The Industrial Maintenance Group
Unit M, Riverside Industrial Estate
Fazeley, Tamworth
B78 3RW, Staffordshire
T 01827 283 322
sales@img-limited.co.uk, www.img-limited.co.uk

1.4. Emergency telephone number

Emergency number : 01827 283 322

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (inhal.), Category 4 H332
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Carcinogenicity, Category 2 H351
Specific target organ toxicity – Repeated exposure, Category 1 H372
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. Harmful if inhaled. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: Cristobalite; Epoxy Polymer; Phenol-Formaldehyde Polymer; Alkyl Glycidyl Ether; Titanium Dioxide

Hazard statements (CLP)

: H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)	H351 - Suspected of causing cancer. H372 - Causes damage to organs through prolonged or repeated exposure. H411 - Toxic to aquatic life with long lasting effects.
	: P201 - Obtain special instructions before use. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P308+P313 - IF exposed or concerned: Get medical advice/attention. P312 - Call a POISON CENTRE or doctor if you feel unwell. P314 - Get medical advice/attention if you feel unwell. P321 - Specific treatment (see supplemental first aid instruction on this label). P391 - Collect spillage.
EUH-statements	: EUH205 - Contains epoxy constituents. May produce an allergic reaction. EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Extra phrases	: Contains Pine oils.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cristobalite	CAS-No.: 14464-46-1	$\geq 10 - < 30$	STOT RE 1, H372
Epoxy Polymer	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119490020-53	$\geq 10 - < 30$	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Phenol-Formaldehyde Polymer	CAS-No.: 9003-36-5 EC-No.: 500-006-8	$\geq 10 - < 30$	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Alkyl Glycidyl Ether	CAS-No.: 68609-97-2 EC-No.: 271-846-8 EC Index-No.: 603-103-00-4	$\geq 2 - < 15$	Skin Irrit. 2, H315 Skin Sens. 1, H317
Titanium Dioxide	CAS-No.: 13463-67-7 EC-No.: 236-675-5	$\geq 2 - < 15$	Carc. 2, H351
BENZYL ALCOHOL	CAS-No.: 100-51-6 EC-No.: 202-859-9	$\geq 2 - < 15$	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332
Pine oils	CAS-No.: 8002-09-3	< 2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Epoxy Polymer	CAS-No.: 25068-38-6 EC-No.: 500-033-5 EC Index-No.: 603-074-00-8 REACH-no: 01-2119490020-53	(5 ≤ C ≤ 100) Eye Irrit. 2; H319 (5 ≤ C ≤ 100) Skin Irrit. 2; H315

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Store locked up.
- Packaging materials : Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Chill-Eze HB LT Part A	
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (OEL TWA)	4 mg/m ³ respirable 10 mg/m ³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Wear a face shield

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves	Polyvinylchloride (PVC)	6 (> 480 minutes)			

Respiratory protection

Respiratory protection:

Wear respiratory protection.

Respiratory protection			
Device	Filter type	Condition	Standard
	Gas/vapour filter		

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Various colours.
Appearance	: Viscous.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 199 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 60 °C

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Auto-ignition temperature	: 315 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: > 20.5 mm ² /s @ 40C
Solubility	: Immiscible with water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 40 Pa @ 20C
Vapour pressure at 50°C	: 2.72 hPa
Density	: 1702.2 kg/m ³
Relative density	: 1.702
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

High temperature. Direct sunlight.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

Chill-Eze HB LT Part A	
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1.5 mg/l/4h
Epoxy Polymer (25068-38-6)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Phenol-Formaldehyde Polymer (9003-36-5)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
Pine oils (8002-09-3)	
LD50 oral rat	3200 mg/kg Source: Corporate Solution From Thomson Micromedex
LD50 dermal rabbit	5000 mg/kg Source: Corporate Solution From Thomson Micromedex
Skin corrosion/irritation	: Causes skin irritation.
Titanium Dioxide (13463-67-7)	
pH	7
Serious eye damage/irritation	: Causes serious eye irritation.
Titanium Dioxide (13463-67-7)	
pH	7
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Epoxy Polymer (25068-38-6)	
NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Cristobalite (14464-46-1)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Epoxy Polymer (25068-38-6)	
NOAEL (oral, rat, 90 days)	50 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other:japanese MITI guidelines for toxicity testing of chemicals
Phenol-Formaldehyde Polymer (9003-36-5)	
NOAEL (oral, rat, 90 days)	≈ 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Chill-Eze HB LT Part A

Viscosity, kinematic	> 20.5 mm ² /s @ 40C
----------------------	---------------------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Epoxy Polymer (25068-38-6)

LC50 - Fish [1]	1.2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	9.4 mg/l Test organisms (species): Scenedesmus capricornutum
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Phenol-Formaldehyde Polymer (9003-36-5)

LC50 - Fish [1]	5.7 mg/l Test organisms (species): Leuciscus idus
LC50 - Fish [2]	> 1000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	3.5 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Titanium Dioxide (13463-67-7)

LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Pine oils (8002-09-3)

LC50 - Fish [1]	18.35 mg/l Source: The ECOTOXicology database
EC50 - Crustacea [1]	24.5 mg/l Source: The ECOTOXicology database

12.2. Persistence and degradability

Chill-Eze HB LT Part A

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Cristobalite (14464-46-1)	
Persistence and degradability	Not rapidly degradable
Epoxy Polymer (25068-38-6)	
Persistence and degradability	Not rapidly degradable
Phenol-Formaldehyde Polymer (9003-36-5)	
Persistence and degradability	Not rapidly degradable
Alkyl Glycidyl Ether (68609-97-2)	
Persistence and degradability	Not rapidly degradable
Titanium Dioxide (13463-67-7)	
Persistence and degradability	Not rapidly degradable
BENZYL ALCOHOL (100-51-6)	
Persistence and degradability	Not rapidly degradable
Pine oils (8002-09-3)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
European List of Waste (LoW, EC 2000/532)	: 20 01 27* - paint, inks, adhesives and resins containing dangerous substances
HP Code	: HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer)	Environmentally hazardous substance, liquid, n.o.s. (Contains Epoxy Polymer)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Contains Epoxy Polymer), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Epoxy Polymer), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special provisions for carriage - Loading, unloading and handling (ADR) : CV13
Hazard identification number (Kemler No.) : 90
Orange plates :



Tunnel restriction code (ADR) : -
EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provisions (IATA) : A97, A158, A197, A215
ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6
Special provisions (ADN) : 274, 335, 375, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6
Special provisions (RID) : 274, 335, 375, 601
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)

Reference code	Applicable on	Entry title or description
3(b)	Chill-Eze HB LT Part A ; Epoxy Polymer ; Phenol- Formaldehyde Polymer ; Alkyl Glycidyl Ether ; BENZYL ALCOHOL	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Chill-Eze HB LT Part A ; Epoxy Polymer ; Phenol- Formaldehyde Polymer ; Pine oils	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH205	Contains epoxy constituents. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Chill-Eze HB LT Part A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

